

Implant compatibility chart



Manufacturer	Implant	Titanium/ Gold-shaded titanium	Zirconia, including ATLANTIS™ Crown Abutment	Screwdriver
BioHorizons	INTERNAL			
	Internal 3.5, 4.5, 5.7	x	x	0.050" (1.25 mm) Hex screwdriver
	Tapered Internal 3.5, 4.5, 5.7	x	x	
	EXTERNAL			
	External Implant 3.5	x		0.050" (1.25 mm) Hex screwdriver
External Implant 4.0, 5.0	x	x		
Biomet 3i	INTERNAL			
	Certain™ 3.25, 4.0, 4/3, 5.0, 5/4, 6.0	x	x	0.048" Hex screwdriver
	Certain™ Prevail™ 3/4/3 (3.4), 4/5/4, 5/6/5, 4/3, 5/4, 6/5	x	x	
	Certain™ XP 4/5, 5/6	x	x	
	EXTERNAL			
	MicroMiniplant™ 3.25	x		0.048" Hex screwdriver
	Miniplant™ 3.25	x	x	
Osseofite™ 3.75, 4.0, 5.0, 6.0	x	x		
Osseofite™ XP 4/5, 5/6	x	x		
Camlog	INTERNAL			
	Screw-line Implant 3.3	x		1.28 mm Hex screwdriver
	Screw-line Implant 3.8, 4.3, 5.0, 6.0	x	x	
	Root-line Implant 3.8, 4.3, 5.0, 6.0	x	x	
DENTSPLY Implants <small>Note: OsseoSpeed™ implants are part of the ASTRA TECH Implant System™</small>	INTERNAL			
	ANKYLOS® C/X 3.5, 4.5, 5.5, 7.0	x	x*	1.0 mm Hex screwdriver
	OsseoSpeed™/OsseoSpeed™ TX 3.0 – Yellow	x		0.050" Hex screwdriver
	OsseoSpeed™/OsseoSpeed™ TX 3.5, 4.0 – Aqua	x	x	
	OsseoSpeed™/OsseoSpeed™ TX 4.5, 5.0 – Lilac	x	x	
	OsseoSpeed™ TX Profile 4.5, 5.0	x	x	
	OsseoSpeed™ 4.0 – Blue (Previous)	x		1.22 mm Hex screwdriver
	XiVE® S 3.0	x		
XiVE® S 3.4, 3.8, 4.5, 5.5	x	x		
Keystone Dental	INTERNAL			
	PrimaConnex™ SD 3.3, 3.5, Genesis™ 3.8	x	x	Keystone Quad Driver
	PrimaConnex™ RD 4.0, 4.1, Genesis™ 4.5	x	x	
	PrimaConnex™ WD 5.0, Genesis™ 5.5, 6.5	x	x	
	EXTERNAL			
	Restore™ SD 3.3, 3.4	x		0.048" Hex screwdriver
	Restore™ RD 3.75, 4.0	x	x	
Restore™ WD 5.0, 5.5, 6.0	x			
Nobel Biocare	INTERNAL			
	NobelActive™ NP 3.5	x	x	Nobel Biocare Unigrip
	NobelActive™ RP 4.3, 5.0	x	x	
	NobelReplace™ NP 3.5	x	x	
	NobelReplace™ RP 4.3	x	x	
	NobelReplace™ WP 5.0	x	x	
	NobelReplace™ 6.0	x	x	
	EXTERNAL			
	Brånemark System™ NP 3.3	x		Nobel Biocare Unigrip
	Brånemark System™ RP 3.75, 4.0	x	x	
	Brånemark System™ WP 5.0, 5.5	x	x	
SteriOss Replace™ 3.1, 3.5, 4.3, 5.0, 6.0	x		0.050" Hex screwdriver	
SteriOss HL™ 3.25, 3.8, 4.5, 5.0, 6.0	x			
Straumann	INTERNAL			
	Bone Level 3.3 NC (Narrow CrossFit™)	x		SCS screwdriver
	Bone Level 4.1, 4.8 RC (Regular CrossFit™)	x	x	
	Standard/Standard Plus 4.8 RN (Regular Neck)	x		
	Standard/Standard Plus 4.8 WN (Wide Neck)	x		
	EXTERNAL			
Standard Plus 3.3 NN (Narrow Neck)	x		SCS screwdriver	
Sybron Implant Solutions	EXTERNAL			
	Endopore 3.5, 4.1, 5.0 - external	x		0.050" Hex screwdriver
	Entegra 3.5, 4.1, 5.0 - external	x		
Zimmer Dental	INTERNAL			
	Tapered Screw-Vent™ 3.5, 4.5, 5.7	x	x	1.25 mm Hex screwdriver
	Screw Vent™ 3.3, 3.7, 4.5	x	x	
	SwissPlus™ 4.8	x		

* Not available for ATLANTIS™ Crown Abutment
All trademarks are the property of their respective owners.

Turnaround times

Turnaround times (in-house business days) for all case sizes		
Titanium	Gold-shaded titanium	Zirconia
2	3	4

Note: Turnaround time listed begins the first business day after receipt of all case information and material required and does not include shipping, which is determined by your choice of delivery method. Turnaround for lab-based scanned cases is one day less than the times shown.

Turnaround times are based on the following:

- Design approvals to process case must be granted by 10 am your local time.
- Lab-scanned cases, including rescans, must be uploaded to ATLANTIS™ WebOrder by 3 pm (EST) in order to save a day of processing compared with the times listed above.
- Material, on-hold and case information issues must be resolved by 8 pm (EST).

Other services

Service	Additional turnaround days
Laboratory services	add 1 day
Provisional restoration	add 5 days
Removable diagnostic preparation	add 2 days

- For the most current implant compatibility, please visit www.atlantisabutment.com or contact Customer Service at 800-531-3481.
- All orders for ATLANTIS™ abutments are shipped with the corresponding abutment screw needed at no extra charge.

Note: The implant manufacturer's recommended torque should always be used when placing the abutment screw.

